

# Safety Data Sheet (SDS)

## Section 1 - Chemical Product and Company Information

Product Name: #205 Carbon and Rust Remover

Product Code: A106

Manufactured/Supplied by:

Sonikor Incorporated  
82 Otis Street  
West Babylon, NY 11704  
Tele: (631) 820-6555

In case of transportation or  
chemical emergency contact:

INFOTRAC: (800) 535-5053 North America  
(352) 323-3500 International

Product Use: Industrial metal cleaning  
Not recommended for: Home use

## Section 2 - Hazards

According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

### GHS Ratings:

Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
Skin corrosive	1A	Destruction of dermal tissue: Exposure < 3 min. Observation < 1 hour, visible necrosis in at least one animal
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5

### GHS Hazards

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

### GHS Precautions

P260	Do not breathe dust/fume/gas/mist/vapours/spray
P264	Wash hands and exposed skin thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P280	Wear protective gloves/protective clothing/eye protection/face protection
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment (see Section 4 on this label)
P330	Rinse mouth
P363	Wash contaminated clothing before reuse
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P301+P330+P331 P303+P361+P353	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P405	Store locked up
P501	Dispose of contents/container in accordance with local/ regional/ national/, regulations.

**Signal Word: Danger**



Preexisting skin, eye, and respiratory disorders may be aggravated by exposure to this product.

### Section 3 - Composition

Chemical Name	CAS number	Weight Concentration %
Sodium Hydroxide	1310-73-2	60.00% - 70.00%
sodium gluconate	527-07-1	20.00% - 30.00%
sodium carbonate	497-19-8	5.00% - 10.00%

### Section 4 - First Aid Measures

**INHALATION** - Take affected persons out into the fresh air. Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

Powder is corrosive to skin and nasal passages. Wipe / rinse out as much as possible.

**EYE CONTACT** - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, remove them if it can be done easily, then flush the eyes with water. Have a physician examine the eyes.

**SKIN CONTACT** - Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

Rinse until skin no longer feels slippery.

If skin irritation continues, consult a doctor.

Launder clothing before reuse.

**INGESTION** - If material is ingested, rinse out mouth with water and seek immediate medical attention. Do not induce vomiting but if vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs. If victim is conscious drink large quantities of water or acidic beverages like soft drinks or citrus juice to dilute / neutralize stomach contents.

Notes to Physician: If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

If necessary oxygen respiration treatment.

## Section 5 - Fire Fighting Measures

Flash Point: None

LEL:

UEL:

**EXTINGUISHING MEDIA:** This product is not inherently flammable. Use media appropriate for surrounding fire.

**UNUSUAL FIRE OR EXPLOSION HAZARDS:** This product generates heat when dissolved in water. It can generate flammable hydrogen gas in contact with aluminum.

**HAZARDOUS COMBUSTION PRODUCTS:** See section 10 for a list of hazardous decomposition products for this mixture.

**FIRE FIGHTING:** If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

**FIRE FIGHTING EQUIPMENT:** Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

## Section 6 - Accidental Release Measures

**SPILL AND LEAK PROCEDURES:** Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Keep nonessential personnel away from the contaminated area. Spilled product may be very slippery! Product absorbs moisture from air and the powders may stick to clothing and equipment. Be careful not to generate dust.

**SMALL SPILLS:** Ventilate the contaminated area. Sweep up spilled material and reuse or dispose of properly. Mop or rinse floor / equipment with water to remove any residue.

Plastic or steel containers are suitable for waste. Do not use aluminum or galvanized steel.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

**LARGE SPILLS:** Ventilate the contaminated area. Carefully sweep up spilled powder for reuse or disposal. Rinse floor and equipment with water to remove any residue.

Transfer swept material to a covered container. Plastic and steel containers are acceptable. Do not use aluminum or galvanized steel containers or tools.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

## Section 7 - Handling and Storage

**HANDLING PRECAUTIONS:** Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate local ventilation at all times to avoid generating product dust. Keep containers closed when not in use. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

Do not allow product to come in contact with aluminum. Do not use aluminum tools for handling.

**STORAGE: Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Provide ventilation for receptacles.

**· Information about storage in one common storage facility:**

Store away from foodstuffs.

Do not store together with acids.

**· Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

**REGULATORY REQUIREMENTS:** No data found.

Section 8 - Exposure Controls / Personal Protection			
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Sodium Hydroxide 1310-73-2	OEL Table z-1 TWA 2.00 mg/m3	TLV 2 mg/m3 (Ceiling)	NIOSH 2.00 mg/m3 (Ceiling)
sodium gluconate 527-07-1	Not Established	Not Established	Not Established
sodium carbonate 497-19-8	Not Established	TLV TWA 3 mg/m3 respirable particles TLV TWA 10 mg/m3 inhalable fraction	Not Established

**ENGINEERING:** Design transfer systems to minimize generation of dust and contact with aluminum.

**VENTILATION:** Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits. Use mechanical ventilation to reduce buildup of vapors and dust in enclosed areas.

**ADMINISTRATIVE CONTROLS:** Read SDS and follow recommended procedures.

**PROTECTIVE EQUIPMENT:** Wear splash goggles. If extra protection is required, wear a face shield over the splash goggles. Face shields are effective only if worn in addition to splash goggles.

Wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material.

Wear chemical-resistant gloves (butyl rubber or neoprene). Protective gloves should be inspected frequently and discarded when they exhibit cuts, tears, pinholes, or signs of excessive wear.

Respiratory protection may not be needed if the local exhaust is sufficient to maintain levels of hazardous ingredients below occupational exposure limits. If needed, use a NIOSH/MSHA approved respirator equipped with a full facepiece, organic vapor cartridges, and high-efficiency, particulate air (HEPA) filters. Do not use respirators beyond their capabilities. FOR EMERGENCIES AND UNKNOWN CONCENTRATIONS, use supplied-air respiratory protection or a positive-pressure, self-contained breathing apparatus (SCBA).

**CONTAMINATED EQUIPMENT:** Launder or clean gear before reuse. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

## Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

<b>Appearance:</b> White powder	<b>Odor:</b> Alkali
<b>Vapor Pressure:</b> N/A	<b>Odor threshold:</b> No Data
<b>Vapor Density:</b> N/A	<b>pH:</b> 14
<b>Specific Gravity:</b> No Data	<b>Melting point:</b> No Data
<b>Freezing point:</b> No Data	<b>Solubility:</b> No Data
<b>Boiling range:</b> No Data	<b>Flash point:</b> None
<b>Evaporation rate:</b> No Data	<b>Flammability:</b> No Data
<b>Explosive Limits:</b> N/A	<b>Partition coefficient (n-octanol/water):</b> No Data
<b>Autoignition temperature:</b> No Data	<b>Decomposition temperature:</b> No Data
<b>Viscosity:</b> No Data	<b>Grams VOC less water:</b> No Data

## Section 10 - Stability and Reactivity

Stability: Hazardous polymerization will not occur.

Components of this mixture are incompatible with the following materials: Acids and soft metals like aluminum. Heat is generated when product comes in contact with or dissolves in water. Contact with aluminum can generate flammable hydrogen gas.

This mixture is likely to exhibit the following combustion products:  
Oxides of carbon and nitrogen

## Section 11 - Toxicological Information

### Mixture Toxicity

Oral Toxicity LD50: 1,200mg/kg  
Inhalation Toxicity LC50: 426mg/L

### Component Toxicity

497-19-8 sodium carbonate  
Oral LD50: 2,800 mg/kg (rat) Dermal LD50: 2,001 mg/kg (rabbit) Inhalation LC50: 1 mg/L (Guin)

Exposure to this material may affect the following organs:

### Effects of Overexposure

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			N/A

## Section 12 - Ecological Information

Ecological information: No data found.

## Component Ecotoxicity

Sodium Hydroxide

Toxicity to fish LC50 - Gambusia affinis (Mosquito fish) - 125 mg/l - 96 h  
LC50 - Oncorhynchus mykiss (rainbow trout) - 45.4 mg/l - 96 h  
Toxicity to daphnia and other aquatic invertebrates Immobilization EC50 - Daphnia (water flea) - 40.38 mg/l - 48 h

sodium carbonate

LC50 fish 1 300 mg/l (96 h; Lepomis macrochirus)  
EC50 Daphnia 1 < 424 mg/l (48 h; Daphnia magna)  
EC50 other aquatic organisms 1 14 mg/l (168 h; Plankton)  
LC50 fish 2 740 mg/l (96 h; Gambusia affinis)  
EC50 Daphnia 2 265 mg/l (48 h; Daphnia magna)  
TLM fish 1 300 ppm (96 h; Lepomis macrochirus)  
TLM other aquatic organisms 1 500 ppm (96 h; Daphnia magna)  
Threshold limit algae 1 242 mg/l (5 days; Algae)

## Section 13 - Disposal Considerations

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

## Section 14 - Transport Information

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
US DOT	Corrosive solids, basic, inorganic, n.o.s.(Sodium hydroxide)	UN3262	II	8

## Section 15 - Regulatory Information

Additional regulatory listings, where applicable.

The following chemicals are listed in MA RTK  
- None

The following chemicals are on the NJ RTK list:  
527-07-1 sodium gluconate 20 to 30 %  
1310-73-2 Sodium Hydroxide 60 to 70 %

The following chemicals are on the NY RTK list  
1310-73-2 Sodium Hydroxide 60 to 70 %

The following chemicals are on the PA RTK list  
527-07-1 sodium gluconate 20 to 30 %  
1310-73-2 Sodium Hydroxide 60 to 70 %

The following chemicals are listed under Prop 65  
- None

**Country**

Canada  
US

**Regulation**

Canadian Domestic Substances List  
Toxic Substances Control Act

**All Components Listed**

Yes  
Yes

**EU Risk Phrases**

**Safety Phrase**

**Toxic Substances Control Act (TSCA):** All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None


Section 16 - Other Information

**Hazardous Material Information System (HMIS)**

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	

**HMIS & NFPA Hazard Rating Legend**  
 \* = Chronic Health Hazard  
 0 = INSIGNIFICANT  
 1 = SLIGHT  
 2 = MODERATE  
 3 = HIGH  
 4 = SEVERE

**National Fire Protection Association (NFPA)**



**DISCLAIMER AND NON-WARRANTY:** This Safety Data Sheet was prepared by Shore Corporation and is correct to the best of our knowledge, information and belief at the date of its publication. The information came from raw material suppliers, regulatory databases, and/or third parties with expertise in this area. This information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. No warranties of any kind, either expressed or implied, including warranties of the accuracy of the information presented and the suitability of a product for a particular purpose

Reviewer Revision

Date Prepared: 6/17/2015